

A

UC949 U.S. PTO
10/30/00

Express Mail No. EL528823204US

Sir:

Transmitted herewith for filing is the patent application of:

Inventors	Larson
Attorney Docket:	D-5013
Title:	Wheel Mounted Power Generator and Wheel Condition Sensing Apparatus

jc927 U.S. PTO
09/702151
10/30/00


Enclosed are: seven (7) sheets of informal drawings (Figs. 1 – 9), and
declaration and power of attorney (unsigned)

The filing fee has been calculated as shown below:

FOR	No. FILED	No. ALLOWED	No. EXTRA	RATE	FEE
BASIC APPLICATION FEE					= \$ 710.00
CLAIMS	16	20	0	x 18	= \$ 0.00
INDEPENDENT CLAIMS	3	3	0	x 80	= \$ 0.00
[] MULTIPLE DEPENDENT CLAIMS PRESENTED				x 270	= \$ 0.00
T O T A L					= \$ 710.00

- ☒ Please charge Deposit Account No. 14-0603 in the amount of \$710.00.
Two duplicate copies of this sheet are enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 14-0603. A duplicate copy of this sheet is enclosed.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 14-0603. A duplicate copy of this sheet is enclosed.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☐ The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).
- ☒ Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Chicago, Illinois 60611
Date: October 30, 2000
Telephone: (312) 836 3023


Jeffrey P. Calfa
Registration No. 37,105

[illegible]

monies uclan

WHEEL MOUNTED POWER GENERATOR AND WHEEL CONDITION SENSING APPARATUS

BACKGROUND OF THE INVENTION

5

Field of the Invention:

The present invention relates to vehicle and wheel assembly condition monitoring and, more particularly, to a hub mounted sensor assembly which is self energized.

10

Description of the Problem:

15

Economical truck operation and the reduction of vehicle maintenance costs are greatly aided by keeping the vehicle in close conformance to a manufacturer's operational specifications. Of particular concern here are those specifications relating to the operating condition of the vehicle axle and tire/wheel assembly. Maintaining proper tire pressure contributes directly to optimum fuel economy and to long tire life. Low tire pressure results in tire sidewall flex which contributes to a heat buildup in the tire. Excessively high tire temperatures promote degradation of the polymers from which tires are constructed which in turn promotes excessive wear of the tire. An axle end temperature which varies above a threshold temperature may indicate the beginning of a wheel bearing problem.

20

25

Truck operators routinely check tire pressure during stops, however, the ability to monitor all of these variables, and possibly to adjust tire pressure, while the vehicle is in motion, would be advantageous.

However, accessibility to points where these variables can be measured, while the vehicle is in motion, is less than optimal. Typical active sensors, such as air pressure gauges and thermometers, work best if they can be placed in close proximity to, if not direct contact with, the object to be measured. On a vehicle, this means placing air pressure sensors onto the rotating wheel. If the condition is to be monitored from the vehicle's cab, some communication device must transfer data from the sensor to a read out device in the cab. On contemporary vehicles, in which instrumentation is highly, if not completely, electronic, this usually means providing power to an electronic sender for the wheel mounted sensor and providing a transmission channel for the data back to the cab.

30

Wheel mounted electronic measurement and transmission systems have been suggested which use batteries installed on the rotating wheels or in the vehicle tire to provide power to signal processing electronics and data transmission. Radio transmission can then be used to provide data transmission to the vehicle cab. Such a system obviously requires occasional checks on battery condition.

5

The prior art also provides for tire repressurization for moving vehicles. An example of such a system which can be mounted on the rotating wheel is United States Patent 5,667,606 to Renier. The Renier device uses a pendulum which hangs freely from a rotating wheel hub. The pendulum is attached to a cam on which a cam follower, attached to a piston which rotates with the hub, rides. As the cam follower rides up on the cam it displaces the piston inwardly until the end of the cam is reached, whereupon the cam follower falls off of the cam and is displaced outwardly by a compression spring in order to begin the cycle again. The piston is the active component of a pump which provides pressurized air to a reservoir which feeds tires is under inflated. The system provides no data transmission to an electronic controller or monitoring arrangement.

10

15

A system which can provide data to a central controller can be integrated with other vehicle control arrangements, or, at a minimum, can be used to alert the driver of a vehicle of out of specification operation. In addition, an electronic system more readily provides monitoring of diverse conditions. Providing such a system on a rotatable wheel with a minimum of additional maintenance concerns remains desirable.

20

SUMMARY OF THE INVENTION

The invention provides an electro-mechanical apparatus suitable for mounting on a vehicle wheel which provides power for sensors and telemetry from sensors on a wheel, including tire temperature and pressure. The apparatus includes a pendulum mounted to rotate freely relative to the vehicle wheel positioned from the wheel hub. When the wheel is set to rotation, the pendulum freely hangs from the wheel hub under the influence of an off center counterweight having sufficient mass to prevent rotation of the pendulum with the wheel. The pendulum is used to position one or more magnets to be used to excite field coils, which are mounted with respect to the wheel hub to rotate with the wheel. The magnets and rotating coils cooperate to energize a power utilization circuit also mounted with respect to the wheel hub to rotate therewith. The utilization circuit may include such sensors as desired, typically including a tire

25

30

pressure gauge and tire and wheel hub temperature gauges. Some embodiments include tire pressurization pumps, which may in turn take one of several forms including solenoid pumps powered indirectly from the rotating coils, or by magnetic button pumps.

5 Additional effects, features and advantages will be apparent in the written description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims.

10 The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

15 Fig. 1 is an exploded perspective view of a wheel sensor assembly in accordance with a preferred embodiment of the invention.

Fig. 2 is a side view in partial cross section of the wheel sensor assembly.

20 Fig. 3 is an exploded view of the wheel sensor assembly.

Figs. 4A-B are views of a magnetic element used in the wheel sensor assembly.

Figs. 5A-B are detailed views of the magnetic element of Figs. 4A-B.

25 Fig. 6 is a block diagram of a power utilization circuit employed in the wheel sensor assembly of the present invention.

Fig. 7 is a block diagram of a power conditioning circuit utilized in the wheel sensor assembly of the present invention.

30 Figs. 8A-B are a schematic illustration of an air pump used in one embodiment of the present invention.

Fig. 9 is a schematic illustration of an air transfer circuit used to deliver pressurized air to tires mounted on a wheel.

5

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings and in particular to Fig. 1, a wheel sensor assembly 10 is illustrated. Wheel sensor assembly 10 is positioned at the end of a wheel axle 12, typically found on a medium or heavy duty truck, and may be used to provide data relating to the operating condition of the axle end and for tires (not shown) mounted on wheels (not shown) depending from the axle 12. Wheel sensor assembly 10 is directed to placing low maintenance energization components, power regulating and signal gathering, conditioning and transmitting circuitry into rotation with the wheels to avoid any need for direct mechanical or electrical connections between the vehicle and the sensor components.

10

15

Wheel sensor assembly 10 is positioned on a backing plate 14, which in turn is mounted on axle 12. Mounting plate 14 is mounted for rotation on axle 12. Backing plate 14 is generally disk shaped and provides points of attachment for a housing 26 of the wheel sensor assembly 10. Housing 26 rotates with the adjacent wheel of the vehicle. A shaft 16 extends outwardly from backing plate 14 relative to axle 12. Shaft 16 mates with a bearing 20 which is positioned in the center of the disk shaped magnetic plate 18. Magnetic plate 18 is set to rotate freely on shaft 16, but tends to keep a fixed rotational position relative to axle 12 under the influence of a relatively substantial inertial mass provide by an off center weight or pendant 22, attached to a face of the plate facing backing plate 14. A plurality of magnets 38 form the other major face of the disk shaped magnetic plate 14. Magnets 38 are flattened, pie section shaped pieces which, when fitted together form a disk facing substantially covering the outer portion of one major surface of magnetic plate 18.

20

25

30

Housing 26 is positioned on backing plate 14 to enclose magnetic plate 18 and a pair of field coils 24 wound on laminate substrate. Field coils 24 are mounted within housing 26 to rotate with the housing and the backing plate. Housing 26 further provides a attachment position for a printed circuit board 32, and a cap or cover 34 enclosing the circuit board. An air pressure sensor 28 and air pressure inlet connection point 30 may also be positioned on the exterior shell of housing 26.

Referring now to Figs. 2-3, backing plate 14 is mounted on one side of an axle end plate 13 facing away from an end to end axle 12. Housing 26 is mounted along rim 84 in a circular recess 86 on the outward face of backing plate 14, and encloses a volume in which shaft 16, magnetic plate 18 and field coils 24 are enclosed. Wheel sensor assembly 10 is illustrated as assembled on backing plate 14. Shaft 16 has a threaded male end 48 which is screwed into a cooperatively threaded receiving bore 49 in back support plate 14 to position the shaft, centered in the exposed major surface and extending perpendicularly from the surface. The opposite end of shaft 16 is a reduced diameter section 47 which mates with a shaft bore 96 defined by bearing 92 (shown in Fig. 5A), which is centered in magnet mounting plate 40.

One or more magnets 38 may be placed on an outward face 41 of magnet mounting plate 40. A magnet 38 and field coil 24, when rotated to bring it adjacent the magnet, should be spaced by gap set to minimize flux leakage without risk of contact between the coil and the magnet. A off center counterweight or pendant 22 is attached to the face of magnet support plate oppositely faced from the face 41. Pendant 22 tends to bring magnetic plate 18 to a substantially fixed rotational position relative to axle 12 with the pendant below and vertically aligned by gravity with the axis of rotation of plate 18. Field coil 24 is mounted to the interior face of wall 54 which defines the shell of housing 26. Where the sensor assembly also provides tire inflation, a magnetic button pump 42 may also be mounted on the interior surface of wall 56. Magnetic button pump 42 is described in greater detail below. A pair of wires 54 is connected between field coil 24 and a printed circuit board 32 which is housed within cover 34. A breather valve 52 allows air to be admitted from exterior of housing 26 via a channel through wall 56 to the interior of housing 26. Tire pressurization valves 50 are also connected by channels 51 running through the interior of housing 26 between pumps, such as pump 42 or solenoid pumps (shown below).

In the exploded view, it may be seen that axle shaft end 11 provides a foundation for mounting backing plate 14. Backing plate 14 comprises two generally disk shaped elements, an larger base plate 13 adapted to provide an interface between the axle shaft end 11 and a mating disk 17 which provides attachment points for housing 26 and shaft 16. Base plate 13 attaches to axle shaft end 11 along a plurality of bolts 64 extended outwardly from the axle shaft end. Bolts 64 are inserted into holes 63 through base plate 13 and the base plate is then secured to axle shaft end 11 by the attachment of nuts 66 to bolts 64.

Prior to positioning base plate 13 on axle shaft end 11, a mating disk 17 is attached to the outwardly oriented face (i.e. the face oriented away from axle shaft end 11) of base plate 13 by a plurality of screws 68 inserted into base plate 13 and mating disk 17 from the inwardly oriented face of foundation disk 13 toward the outwardly oriented face. The backing plate 14 formed by the assembly of the base plate 13 and the mating plate 17 then is assembled as a group onto axle shaft end 11.

Magnetic plate shaft 16 is screwed at its threaded end 48 into a cooperatively threaded hole 49 in mating disk 17. The opposite end of shaft 16 is a reduced radius end 47 onto which a magnet mounting plate 40 of magnetic plate 18 is positioned. Mounting plate 40 is retained on shaft 16 by a washer 46, which is placed over end 47 and an opening through plate 40. A screw 78 is then placed through the washer and into shaft 47 to pin magnetic plate 40 on shaft 16. As described below, magnetic plate 40 incorporates a bearing allowing magnetic plate 40 to freely rotate on reduced end 47 of shaft 16.

Housing 26 encloses magnetic plate 18 and magnetic plate shaft 16 upon positioning of the circumferential rim 84 defining an edge to housing 26 into a circular channel 86 in the outer face of mating disk 17. A notch 101 is situated along the interior edge of the rim. Notch 101 provides a nesting spot for an O-ring 59 which is pressed between the faces of the notch and the interior edge of circular channel 86 to seal housing 26 against mating disk 17. Screws 68, inserted from inward face of base plate 13, through the base plate and mating disk 17 into receiving holes 82 at the bottom of the circumferential rim 84 lock the housing 26 onto the backing plate 14. Counterweight 22, which is fixed to the inward face of magnet support plate 40, pulls the plate to a rotational position with the counterweight or pendant vertically below shaft 16. Backing plate 14 and shaft 16 will rotate when a wheel mounted to axle shaft end 11 rotates. Under the influence, and inertia, of the mass of counterweight 22, magnetic plate 18 does not turn with the wheel, but remains substantially stationary with the counterweight below the (turning) shaft 16.

A printed circuit board 32 is affixed to the outward oriented shell top of housing 26. Bolts 88 are mounted through the circuit board 32 into wall 56 of housing 26 to retain the circuit board on the housing. Various circuit components 80 and electro-mechanical components, including solenoid pump 72 are mounted onto one face of circuit board 32 in a conventional manner. Solenoid pump 72 (if used) delivers pressurized air to tire pressure valves 50 along air lines 73 and 75 to channels 76 and 77, respectively. Other types of pumps may be used, such as a magnetic button pump mentioned above.

Circuit board 32 is closed within a Lexan cover 34 which fits over the circuit board and mates with the outward wall section of housing 26. An O-ring 58, fitted between the cover and the housing, seals the cover against the housing 26. A plurality of screws 90 fitted through a rim to the cover 34 into housing 26 retain the cover against the housing.

5

Referring now to Figs. 4A-B and Figs. 5A-B, magnetic plate 18 is described in greater detail. Magnetic plate 18 is constructed on a magnet support plate 40, which is a flattened disk shaped member with a hole 96 centered on the axis of symmetry of the disk which passes through the disk from major surface to major surface. In a preferred embodiment, eight flattened, pie section shaped magnets 38 are disposed on one face of magnet support plate 40. Magnets 38 are arranged circumferentially around the perimeter of the major surface of the magnet support plate 40 and may be affixed thereto by gluing, or fasteners fitted through holes 94. Magnets 38 are oriented to present a pole on their exposed surfaces oriented away from the magnet support plate 40. The poles alternate in polarity, so that as they pass by a field coil 24 potentials of alternating polarity are produced on the coil.

10

15

Hole 96 is lined with an antifriction bearing 92 which fits around narrowed end 47 of shaft 16. Magnet support plate 40 freely rotates on bearing 92. The exterior of bearing 92 provides a support for a washer 46 used in retaining magnetic plate 18 on shaft 16. Pendant, or counterweight 22, is positioned on the opposite major surface of magnet support plate 40 as magnets 38. Counterweight 22 must be sufficiently massive to prevent magnetic coupling between one of magnets 38 and a magnet piston from a magnetic button pump resulting in the magnetic plate 18 rotating with housing 26.

20

Fig. 6 illustrates a power utilization circuit 100 which provides for the collection, conditioning and transmission of data from sensors. Separate pressure sensors 102, 104 are provided for each tire (not shown). A temperature sensor 106 may be placed in communication with the air within the tires to provide an indication of tire temperature. A hub temperature sensor 108, based on an air temperature sensor within housing 26 or within cover 34, may be provided. Conventional amplification and digital to analog conversion circuitry (signal conditioning circuits) 110 is provided for each signal.

25

The signals from each of the conditioning circuits 110 is routed through a multiplexer 112 under the control of a microcontroller 114, which can select which signal to pass to a transmitter 116 for broadcast to a remote receiver 117 located elsewhere on a vehicle. In some embodiments transmitter 116

30

may be replaced with a transceiver as a CAN (controller area network) remote receiver 117. In such cases remote commands such as to began inflation of a tire may be returned to microcontroller 114. Microcontroller 114 may control actuation of a switch 172 which in time controls powering a solenoid pump 72. Such signals commanding increased pressurization may come upon indication from other sources that the vehicle is carrying an especially heavy load.

Fig. 7 illustrates the power supply circuitry 120 used to power the utilization circuitry 100 and the solenoid pump 72, if used. A field coil 24 is connected to a conventional rectifier 122 and filter 124 arrangement to supply voltage at a selectable level to a switching regulator 126. Since power is rectified and filtered, the utilization circuitry remains energized regardless of the direction of movement of the vehicle. Switching regulator 126 supplies power to a 5-volt regulator 128, which in turn powers the components of the utilization circuitry 100. A solenoid pump 72 receives power from capacitor 124 when switch 172 closes.

Figs. 8A-B illustrate two pumps usable with the invention. Magnetic button pump 42 may be used instead of solenoid pumps, reducing power demands on the power supply circuitry 120. Magnetic button pump 42 comprises a magnetic button piston 44 retained for linear reciprocation in a cylinder 150. A diaphragm 161 seals the piston 44 against the interior wall of cylinder 150. Magnetic button piston 44 is retained within cylinder 150 by a lip positioned at one end of cylinder 150. An opening 136 allows air to freely move into and out of the portion of cylinder 150 between piston 44 and the opening. Piston 44 reciprocates under the influence of magnetic poles of alternating polarity of magnets 38 passing close over opening 136. As piston 44 is drawn toward opening 136, air is pulled into cavity 151 through a one way check valve 130. As piston is pushed away from opening 136 air is forced under pressure through an outlet provided by a one way check valve 132.

Solenoid pump 72 is constructed similarly to button pump 42. However, instead of magnets 38 providing reciprocation of piston 44, a solenoid 155 wrapped on cylinder 150 effects movement of magnetic piston 44. Indeed, in a solenoid pump piston 44 may be unmagnetized iron. Fig. 9 illustrates a pressurization circuit usable with either type of pump. A pump 160 provides air under pressure to a Schrader valve 136, to which tubing connecting the sensor assembly 10 to the tires may be provided. As illustrated a single pressure sensor 102B, positioned in the circuit between the Schrader valve and a Y-connection splitting the delivery of air to the two tires, indicates back pressure in the system when air is

delivered. A pressure sensor situated here displays data which in effect is an average of the pressures in the two tires. Alternatively, separate sensors may be placed in each circuit downstream from check valves 140, which prevent over pressurization of the tires.

5 The invention provides a sensor system which can be powered without use of a battery or direct external connection while mounted on a rotating wheel hub. The system returns data to a central controller and can be integrated with other vehicle control arrangements. Alternatively, a minimum system can be deployed to alert the driver of a vehicle of out of specification operation.

10 While the invention is shown in only one of its forms, it is not thus limited but is susceptible to various changes and modifications without departing from the spirit and scope of the invention.

What is claimed is:

1. An electromechanical apparatus, comprising:
 - (a) a vehicle wheel adapted for axial rotation;
 - (b) a pendulum mounted to rotate freely relative to the axis of rotation for the vehicle wheel;
 - (c) a magnetic element mounted with and positioned by the pendulum;
 - (d) a least a first generator coil mounted to the wheel for rotation with the vehicle wheel to pass through lines of flux associated with the magnetic elements;
 - (e) a current utilization circuit mounted on the vehicle wheel and connected to at least the first generator coil.
2. An electromechanical apparatus as claimed in Claim 1, wherein the magnetic element comprises a plurality of magnets oriented so that their magnetic poles alternate in direction with adjacent magnets.
3. An electromechanical apparatus as claimed in Claim 1, further comprising a plurality of electrical coils mounted on the vehicle wheel.
4. Our electromechanical apparatus as claimed in Claim 2, further comprising:
 - (a) an air pump.
5. An electromechanical apparatus as claimed in Claim 4, wherein the pump is a magnetic button pump.
6. An electromechanical apparatus as claimed in Claim 4, wherein the pump is a solenoid pump.
7. An apparatus for monitoring physical variables of a tire and an axle, the apparatus comprising:
 - (a) a vehicle wheel having a hub mounted for rotation on the axle, the tire being mounted thereon;
 - (b) a tire pressure gauge mounted on the vehicle wheel in communication with the tire;
 - (c) a tire temperature gauge mounted on the vehicle wheel adjacent the tire;
 - (d) an axle temperature gauge mounted on the vehicle wheel adjacent the wheel hub;
 - (e) a signal processor and transmitter mounted on the vehicle wheel and connected to the tire pressure gauge, the tire temperature gauge and the axle temperature gauge for collecting

- data from the gauge and broadcasting a radio signal comprehending values representing the data; and
- (f) an energization assembly including a magnetic element mounted adjacent the vehicle wheel presenting at least one magnetic pole parallel to the vehicle wheel's axis of rotation, a field coil mounted on the vehicle wheel to pass the magnetic pole periodically to induce excitation therein, and electrical filtering and supply circuitry connected to the field coil and to the signal processor and transmitter.
8. An apparatus as claimed in Claim 7, wherein the magnetic element further comprises a positioning segment depending from the wheel hub and a stabilizing element for resisting rotation of the positioning segment with the vehicle wheel.
9. An apparatus as claimed in Claim 8, wherein the positioning segment includes a mounting plate centered on the axis of rotation of the vehicle wheel; a low friction bearing centering the mounting plate on the hub;
10. An apparatus as claimed in Claim 9, wherein the stabilizing element includes an off center weight attached to the mounting plate providing inertial resistance to rotation of the mounting plate.
11. An apparatus as claimed in Claim 10, wherein the magnetic element comprises:
- (a) the mounting plate being a disk mounted to have major opposed surfaces perpendicular to the axis of rotation of the vehicle wheel; and
 - (b) a plurality of magnets shaped as wedges and arranged circumferentially around the outer edge of the major surface of the disk closer to the vehicle wheel with their poles oriented to alternate with adjacent magnets.
12. Apparatus comprising:
- (a) a vehicle wheel having an axis of rotation;
 - (b) a magnetic element positioned adjacent the vehicle wheel and oriented with respect to the vehicle wheel to project lines of flux;
 - (c) a generator coil mounted with respect to the vehicle wheel to rotate therewith, and to intercept the line of flux;


- (d) electrical utilization elements mounted with respect to the vehicle wheel to rotate therewith and connected to the generator coil to receive energization therefrom.
13. Apparatus as claimed in Claim 12, wherein the magnetic field source further comprises:
- (a) a free wheeling plate having a major surface, rotatably mounted with respect to the vehicle wheel and positioned so that a major surface lies parallel to the vehicle wheel and perpendicular to the axis of rotation of the vehicle wheel; and
 - (b) a plurality of magnets mounted on the major surface of the plate and oriented to present poles of alternating magnetic polarity outwardly from the major surface.
14. Apparatus as claimed in Claim 13, wherein the electrical utilization elements include sensors and an air compressor.
15. Apparatus as claimed in Claim 14, further comprising an air compressor mounted to rotate with the vehicle wheel and energized by the generator coil.
16. Apparatus as claimed in Claim 15, an air compressor mounted with respect to the vehicle wheel to rotate therewith and oriented to be directed activated by the plurality of magnets.

ABSTRACT OF THE DISCLOSURE

An electromechanical apparatus suitable for mounting on a vehicle wheel power for generating telemetry relating to the wheel including tire temperature and pressure. The apparatus includes a pendulum mounted to rotate freely relative to the vehicle wheel which is positioned from the wheel hub.

When the wheel is set to rotation, the pendulum freely hangs from the wheel hub under the influence of an off center counterweight having sufficient inertia to prevent rotation of the pendulum with the wheel.

The pendulum is used to position one or more magnets to be used to excite field coils, which are mounted with respect to the wheel hub to rotate with the wheel. The magnets and rotating coils cooperate to energize a power utilization circuit also mounted with respect to the wheel hub to rotate therewith. The utilization circuit may include such sensors as desired, typically including though a tire pressure gauge and tire and wheel hub temperature gauges. The apparatus is readily extended to incorporate a tire pressurization pump, which may be a solenoid pump powered indirectly from the rotating coils, or by a magnetic button pump.



0.5000

D5013

UNIT EXPLODED VIEW

3/7




Fig 3

D5013

4/7




Fig. 4





Fig. 4A

18

D5013

000007 19120260

5/7



D5013

MAGNETIC CONFIGURATION W/ COUNTER BALANCE

6/7




Fig. 6






Fig. 7

D5013

7/7

FIG. 8B



D5013

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

+

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	D-5013	
	First Named Inventor	Larson	
	COMPLETE IF KNOWN		
	Application Number	/	
	Filing Date		
	Group Art Unit		
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	
		Examiner Name	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Wheel Mounted Power Generator and Wheel Condition Sensing Apparatus

the specification of which *(Title of the Invention)*

☒ is attached hereto
OR
☐ was filed on (MM/DD/YYYY) [] as United States Application Number or PCT International Application Number [] and was amended on (MM/DD/YYYY) [] (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

(Page 1 of 2)

Burden Hour Statement This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington, DC 20231.

+

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00 OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer Number Bar Code label here

Name	Registration Number	Name	Registration Number
SULLIVAN, DENNIS KELLY	26,510	GILBERTO HERNANDEZ	46,483
CALFA, JEFFREY P.	37,105		
POWELL, NEIL T.	45,020		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto

Direct all correspondence to: ☐ Customer Number OR ☒ Correspondence address below

Name	INTERNATIONAL TRUCK AND ENGINE CORPORATION				
Address	455 North Cityfront Plaza Drive				
Address	Suite 1300				
City	Chicago	State	IL	ZIP	60611
Country	USA	Telephone	312-836-2311	Fax	312-836-3982

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))		Family Name or Surname			
Gerald L.		Larson			
Inventor's Signature				Date	
Residence: City	Fort Wayne	State	IN	Country	USA
				Citizenship	USA
Post Office Address	9603 W. Cove Court				
Post Office Address					
City	Fort Wayne	State	IN	ZIP	46804
				Country	USA

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto